


Stock to compare

ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

GEN 1 STOCK

Event	
a (EX)	240
b(IN)	248
c(IO)	7
d(IC)	61
e(EC)	9
f(EO)	51
g*(EX)	0.365
h*(IN)	0.396
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL

* GROSS LIFT


Stock to compare

ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

GEN 2 STOCK

Event	
a (EX)	240
b(IN)	240
c(IO)	3
d(IC)	57
e(EC)	9
f(EO)	51
g*(EX)	0.365
h*(IN)	0.365
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL

* GROSS LIFT


Stock to compare

ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

GEN 3 STOCK

Event	
a (EX)	240
b(IN)	232
c(IO)	-1
d(IC)	53
e(EC)	9
f(EO)	51
g*(EX)	0.365
h*(IN)	0.340
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL

* GROSS LIFT




ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

ASER1-990S3

Event	S3
a (EX)	260
b(IN)	260
c(IO)	13
d(IC)	67
e(EC)	19
f(EO)	61
g*(EX)	.442"
h*(IN)	.442"
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL

* GROSS LIFT




ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

ASER1-990S4

Event	S4
a (EX)	266
b(IN)	266
c(IO)	16
d(IC)	70
e(EC)	22
f(EO)	64
g*(EX)	.464"
h*(IN)	.464"
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL

* GROSS LIFT




ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

ASER1-0S4HL

Event	S4 HL
a (EX)	266
b(IN)	266
c(IO)	16
d(IC)	70
e(EC)	22
f(EO)	64
g*(EX)	.488"
h*(IN)	.488"
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL

* GROSS LIFT




ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

ASER1-C10C1

Event	C1
a (EX)	264
b(IN)	264
c(IO)	15
d(IC)	69
e(EC)	21
f(EO)	63
g*(EX)	0.476"
h*(IN)	0.476"
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL
MUST USE JWT SPRINGS

* GROSS LIFT




ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

ASER1-C20C2

Event	C2
a (EX)	275
b(IN)	275
c(IO)	20.5
d(IC)	74.5
e(EC)	26.5
f(EO)	68.5
g*(EX)	0.500"
h*(IN)	0.500"
I L/C	117
E L/C	111
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL
MUST USE JWT SPRINGS

* GROSS LIFT




ENGINE TYPE: SR20DE HYDRAULIC

CAM TIMING SPEC. FOR:

ASER1-C30C3

Event	C3
a (EX)	285
b(IN)	285
c(IO)	27.5
d(IC)	77.5
e(EC)	33.5
f(EO)	71.5
g*(EX)	.526"
h*(IN)	.526"
I L/C	115
E L/C	109
COLD VALVE LASH:	
INT	NA
EXH	NA



USE FACTORY MANUAL
MUST USE JWT SPRINGS

* GROSS LIFT